

Pocket LOOX 700 Series The mobile business navigator

Issue December 2004

Pages 2

The Pocket LOOX 700 Series is the new innovative handheld from Fujitsu Siemens Computers: latest features and high-performance Intel technology integrated in a very small and stylish form factor cabinet.

State-of-the-art functionality like integrated camera¹⁾ and a brilliant VGA resolution²⁾ make the Pocket LOOX 700 Series the ideal mobile life companion for professional and private users: never miss any appointment again, manage your contacts, send and receive e-mails, and get connected with your office data while on the move.

The Pocket LOOX 700 is designed as an open platform for mobility solutions. Thanks to its flexible connectivity, mobile applications, like accessing data on a SAP server, secure VPN solutions or thin client based mobility solutions can be easily implemented. Fujitsu Siemens Computers can offer support in finding the right mobile solution for you and your business.

Mobility

- Stylish, high-end design for every profile – in and out of the office
- Small size to fit into every pocket
- Wireless data transmission wherever you are via Bluetooth³⁾ and WLAN
- High expandability due to integrated SD/MM card slot and CF card slot for even more mobile functions
- Broad range of accessories like GPS navigation kit, GSM/GPRS, CF/SD memory cards or battery
- CONNECTMOBILITY-E2C connection manager for convenient access

Reliability

- Mechanical and functional stability
- Long battery time:
May even be extended by additional batteries, easily exchanged while your data remains safe
- Variety and choice of different software applications with enclosed software voucher

Security

- Automatic password protection when powered off (depending on operating system settings)
- Flashable ROM (LOOXstore) to save your data in case of hard reset
- Optional VPN solutions for secure data transaction

Ergonomics

- Enjoy the viewing quality of the brilliant transfective color TFT TouchScreen display for indoor and outdoor use
- Brilliant VGA or QVGA for perfect viewing experience depending on model
- Integrated camera to catch reality with Pocket LOOX 720
- Advanced one hand use with Fujitsu Siemens Computers SpeedMenu
- Fast access to your favorite applications through programmable buttons

1) for Pocket LOOX 720 only

2) for Pocket LOOX 718 and 720

3) ActiveSync and certain profiles are dependant on third party Bluetooth hardware capabilities. Please check profile availability on remote device to ensure compatibility. Fujitsu Siemens Computers Bluetooth dongle is recommended for maximum device compatibility (order code: S26391-F2461-L200).



System	Pocket LOOX 710	Pocket LOOX 718	Pocket LOOX 720
Applications processor	Intel® PXA272 with 64 MB stacked Tyax flash memory with 416 MHz	Intel® PXA272 with 64 MB stacked Tyax flash memory with 520 MHz	
Memory	System memory: 64 MB Flash memory: 64 MB (rd 28 MB usable as LOOXstore)	System memory: 128 MB Flash memory: 64 MB (rd 28 MB usable as LOOXstore)	
Display	3.5-inch QVGA 320 x 240 pixel transflective TFT TouchScreen, 65.536 colors, LED backlight	3.6-inch VGA 640 x 480 pixel transflective TFT TouchScreen, 65.536 colors, LED backlight	
Camera	-	-	1.3 Megapixel; integrated picture and video capturing with integrated flash
Dimensions (H x W x D)	122 x 72 x 16.1 mm	122 x 72 x 15.2 mm	
Weight	Approx. 180 grams	Approx. 170 grams	

Interfaces

1 x built-in microphone
1 x speaker, 1 x receiver for VoIP calls
1 x headphone jack (3.5 mm)
1 x IrDA (Consumer Infrared)
USB via sync cable (1.1 slave, 1.1 host)
Serial (RS232) via sync cable (DSR / DTR supported)

Bluetooth module

1.2 Power class 2
Profiles*
BNEP, DUN-DT, FT-Client,
GAP, File Transfer, Object
Push, OPP Client, Point to
Multipoint (PAN), FT-Server,
LAN-DT, Point to Point (LAP),
OPP Server, PAN-User, SDAP,
SDP, SerialDevA, SerialDevB

Wireless LAN module

Vendor TI
Type 1100
Spec IEEE802.11b (Wi-Fi)

Expansion slots

SD I/O -MM card
Compact Flash type II slot

Battery

Exchangeable battery, Lithium-Ion, rechargeable
Main battery capacity 1640 mAh
Buffer battery,
max. time for battery exchange 30 min

Power supply

Rated voltage 110 – 240 V
Power cord with EU plug, UK plug
additionally available,
standard in UK versions

Operating time

Standby (full loaded) 350 h
Working (depending on usage) 12 h

Import and usage of wireless technologies

According to country specific regulations

Ergonomics

3-way up-down-enter jog dial
Fujitsu Siemens Computers SpeedMenu button
4 programmable application buttons
Voice Recorder button
5-way Navigation button

Operating system

Microsoft Windows Mobile™ Software 2003 for Pocket PC
Second Edition

Applications

Fujitsu Siemens Computers SpeedMenu
Fujitsu Siemens Computers Key lock
Fujitsu Siemens Computers Backup
Fujitsu Siemens Computers CONNECTMOBILITY-E2C
Fujitsu Siemens Computers Panning
Pocket Outlook, Pocket Word, Pocket Excel, Calculator
MSN® Messenger
Pocket Internet Explorer
Windows Media® Player 9 for Pocket PC
Pictures
Terminal Services Client
Jawbreaker™
Voice recorder
Display change from Portrait to Landscape mode
Microsoft Active Sync 3.7.1
supports Microsoft Outlook 98, 2000, 2002, 2003, XP
Software voucher for software download with prepaid license
fee

Standard delivery package

Handheld device
USB docking station
Carrying case
USB client/host sync cable
AC adapter with cable (country specific EU/UK)
Microsoft Companion CD
Getting started (printed manual)
Safety instructions and warranty flyer
Easy Guide on CD
Warranty manual on CD
Software Voucher

Options / accessories

SD/MM and CF cards
Main battery
GPS navigation kit
Leather cases
USB docking station
Stylus / SD slot cover pack
AC adapter, car adapter
USB sync cable
Additional Software available at
<http://www.PocketLoox-Choice.com> or
<http://www.PocketLoox-Choice.de>

* ActiveSync and certain profiles are dependant on third party Bluetooth hardware capabilities. Please check profile availability on remote device to ensure compatibility. Fujitsu Siemens Computers Bluetooth dongle is recommended for maximum device compatibility (order code: S26391-F2461-L200)